

## Extend Heavy Duty Multi-Fleet Pre-Mix Coolant (EXCOOL)

Nulon EXTEND Heavy Duty Multi-Fleet Coolant is premixed with high quality demineralised water at a 50/50 coolant to water ratio and requires no further dilution. The ethylene glycol coolant base is combined with a hybrid mixture of advanced organic and inorganic inhibitor chemistry to provide superior anti-freeze, anti-boil, cavitation, and corrosion protection for all types of earthmoving and construction equipment.



### APPLICATIONS

Nulon EXTEND Heavy Duty Multi-Fleet Coolant is premixed with high quality demineralised water at a 50/50 coolant to water ratio and requires no further dilution. The ethylene glycol coolant base is combined with a hybrid mixture of advanced organic and inorganic inhibitor chemistry to provide superior anti-freeze, anti-boil, cavitation, and corrosion protection for all types of earthmoving and construction equipment.

Nulon EXTEND is recommended where the following industry standards or manufacturer's specifications are cited:

- Australian Standard – AS/NZ 2108:2004 (Type A)
- American Society for Testing and Materials - ASTM D3306, D4985, D6210
- Japanese Industrial Standards - JIS-K-2234
- Caterpillar EC-1
- Cummins CES 14603
- Case MS 1710
- MTU MTL 5048
- Ford ESE-M97B18-C
- General Motors GM-1899M
- Toyota Long Life Coolant
- Volvo Original Coolant

### DIRECTIONS OF USE

Nulon EXTEND Heavy Duty Multi-Fleet Coolant is premixed and ready to use. Refer to your equipment maintenance manual for cooling system capacity, drain and fill instructions.

Replace Nulon EXTEND Heavy Duty Multi-Fleet Coolant at the service interval recommended by your equipment manufacturer, or at the default interval of 8 years or 12,000 hours of use (whichever occurs first). Suitable for use as a top up of red heavy duty diesel coolants. When topping up the service life defaults to that of the original coolant. If you are unaware of the type or service life of the coolant in the system, we recommend a complete coolant change to Nulon EXTEND Heavy Duty Multi-Fleet Coolant.

### SAFETY DIRECTIONS

**SAFETY:** Wash hands, face and all exposed skin thoroughly after handling. Wear protective gloves, eye/face protection. Avoid breathing mist, vapours or spray.

**FIRST AID:** IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth. IF INHALED: Remove person to fresh air and keep comfortable for breathing. For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor (at once).

**ENVIRONMENT:** Do not pollute drains, soil or water with used products. After use, dispose of container in a responsible manner. Disposal of container should comply with local council regulations.

### Pack Sizes



Part No: EXCOOL-20  
20 litres - Single Unit  
Barcode: 9311090006317



Part No: EXCOOL-205  
205 Litre Drum - Single Unit  
Barcode: 9311090006324



Part No: EXCOOL-1000  
1000 Litres - Single Unit  
Barcode: 9311090006331