

TITAN CARGO FLEX K-4 10W-40

TITAN CARGO FLEX K-4 10W-40 is a Premium Low-SAPS Long Drain engine oil for light and heavy-duty commercial vehicles.

Description

TITAN CARGO FLEX K-4 10W-40 is a Premium Low-SAPS Long Drain engine oil for light and heavy-duty commercial vehicles, offering maximum fuel economy over the whole drain-interval due to its outstanding oxidation and ageing stability. TITAN CARGO FLEX K-4 10W-40 also supports optimum protection for the latest diesel particulate filters and catalysts, and due to minimum evaporation loss, the oil consumption and turbocharger deposits are significantly reduced.

Application

TITAN CARGO FLEX K-4 10W-40 is specially developed for long drain intervals in commercial vehicles with modern exhaust gas treatment systems. Because of the extensive performance profile, TITAN CARGO K-4 10W-40 covers both European, Japanese and North American vehicles and is additionally suitable as a rationalization product for older vehicles. TITAN CARGO FLEX K-4 10W-40 completely fulfils all latest ACEA Ex specifications in combination with API CK-4. TITAN CARGO FLEX K-4 10W-40 is miscible and compatible with conventional branded engine oils. In order to fully utilize the product's benefits, mixing with other engine oils should be avoided and a complete oil change is recommended when converting to TITAN CARGO FLEX K-4 10W-40. For information on product safety and proper disposal please refer to the latest Safety Data Sheet.

Advantages/Benefits

- Suitable for European, Japanese heavy-duty vehicles with latest specifications
- Long drain application due to strong oxidative performance
- Product rationalisation benefits as can be used in older vehicles
- Suitable for low emission equipment such as diesel particulate filters and catalysts.
- Excellent wear protection even under high operation conditions.

Specifications

- API CK-4/CJ-4
- ACEA E11/E8/ E9/E7/E6
- CAT ECF-3

Approvals

- DEUTZ DQC IV-18 LA
- MACK EOS-4.5
- VOLVO VDS 4.5
- MAN M 3775
- MB-APPROVAL 228.51
- RENAULT RLD-3

FUCHS Recommendations

- CUMMINS CES 20086
- DETROIT DIESEL 93K222
- JASO DH-2

Product Information



CHARACTERISTICS

SAE Grade	SAE J300	N/A	10W-40
Kinematic Viscosity @ 100 Deg C	ASTM D445	15.0 Typical	cSt
Viscosity Index	ASTM D2270	>140	N/A
Density @ 15 Deg C	DIN 51757	0.86	kg/L
High Temperature High Shear (HTHS)	ASTM D4683	>3.5	N/A

Product Code: M5126005
Last Update: 29/08/2023