

TITAN FORMULA SP SEM 10W-30

A high performance engine lubricant utilising molecularly converted baseoil designed for petrol, LPG & light duty diesel engines.

Description

TITAN FORMULA SP SEM 10W-30 is a high performance, all season, fuel economy engine oil designed for normally aspirated and turbocharged cars and vans with petrol engines. Meets the following performance requirements: API SP / CF and ILSAC GF-6A

Application

Miscible with all mineral and synthetic oils, therefore no flushing is required. In order to obtain the full benefits of TITAN FORMULA SP SAE 10W-30 please drain the system fully and refill with TITAN FORMULA SP SEM 10W-30.

Advantages/Benefits

- A stay-in grade lubricant, which maintains wear protection and fuel economy characteristics even in severe conditions

- Absolute minimum oil consumption and evaporation loss due to the high quality of the base oil
- Lowered fuel consumption due to meeting the latest ILSAC GF-6A performance levels
- Outstanding wear protection, minimised deposits and sludging as part of meeting the latest API SP performance levels

Specifications

- API SP / CF

Approvals

FUCHS Recommendations

Product Information



CHARACTERISTICS

Density @ 15 Deg C	DIN 51757	0.86	Kg/L
Viscosity Index	ASTM D2270	> 135	N/A
Kinematic Viscosity @ 100 Deg C	ASTM D445	10.5 typ.	cSt
High Temperature High Shear (HTHS)	ASTM D4683	> 2.9	N/A

Product Code: M5084000
Last Update: 25/05/2022