

TITAN FORMULA SP SEM 10W-40

A high performance engine oil with exceptional oil consumption control properties and excellent protection against wear and piston deposits.

Description

TITAN FORMULA SP SEM 10W-40 is a high performance, all season SAE 10W-40 fuel economy engine oil for use in normally aspirated and turbocharged petrol and diesel engines in cars and vans. Meets the following performance requirements: API SP/CF

Application

Product is miscible with all mineral and synthetic oil and therefore no flushing is required. In order to obtain the full benefits of TITAN FORMULA SP SEM 10W-40 please drain and refill the system with TITAN FORMULA SP SEM 10W-40

Advantages/Benefits

- A stay-in grade lubricant, which maintains its wear protection and fuel economy

characteristics even in the most severe conditions

- Absolute minimum oil consumption due to low evaporation losses resulting from the outstanding quality of the base oil and additive technology
- Meets the latest requirements of API SP.

Specifications

- API SP / CF

Approvals

FUCHS Recommendations

Product Information



CHARACTERISTICS

| | | | |
|------------------------------------|------------|-----------|------|
| Density @ 15 Deg C | DIN 51757 | 0.86 | kg/L |
| Kinematic Viscosity @ 100 Deg C | ASTM D445 | 14.5 typ. | cSt |
| Viscosity Index | ASTM D2270 | > 145 | N/A |
| High Temperature High Shear (HTHS) | ASTM D4683 | > 2.9 | N/A |

Product Code: M5085000
Last Update: 25/05/2022