

## TITAN SINTOPOID LS SAE 75W-140

**Fully-synthetic, high-performance gear oil for axles and transfer gear-boxes**

### Description

TITAN SINTOPOID LS SAE 75W-140 is a fully synthetic, high-performance gear oil for the use in highly loaded axle and transfer gearboxes equipped with either conventional or limited slip differentials

### Application

TITAN SINTOPOID LS SAE 75W-140 complies with the wear protection requirements of API GL-5 and is suitable for the use in hypoid drives even under highest stress. Due to the additive chemistry used with LS-capable components (Limited Slip) the product can be used in both conventional and limited slip differentials.

TITAN SINTOPOID LS SAE 75W- 140 can be used in vehicles where a lubricant of this quality is specified. TITAN SINTOPOID LS SAE 75W-140 is miscible and compatible with conventional branded YYY-oils. However, mixing with other gear oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when converting to TITAN SINTOPOID LS SAE 75W-140.

For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

### Advantages/Benefits

- Allows increased drain intervals
- Excellent resistance against shear and ageing
- Good low temperature properties
- Less deposits due to excellent high temperature stability
- Outstanding wear protection even under severe conditions
- Particularly effective resistance to highest loads

### Specifications

- API GL-5

### Approvals

- -

### FUCHS Recommendations

- BMW 83 22 2 282 583
- BMW 83 22 9 407 870
- CHRYSLER MS-8985
- FORD M2C192-A
- GM 12346140
- JOHN DEERE JDM J 11 G
- SCANIA STO 1:0

# Product Information



## CHARACTERISTICS

Density @ 15°C	DIN 51 757	0.814	kg/m3
Flashpoint (COC)	DIN ISO 2592	200	°C
Pour Point	DIN ISO 3016	-48	°C
Kinematic viscosity at 40°C	DIN 51 562-1	170	mm2/sec
Kinematic viscosity at 100°C	DIN 51 562-1	25	mm2/sec

Product Code: 4357  
Last Update: 08/06/2017