



# TECHNICAL DATA SHEET

## A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

Issued: March 2020

## DEOX R56 Multi-Purpose Super Lubricant

PART NUMBER	AVAILABLE SIZE
CT-R56-150G	150g Aerosol
CT-R56-300G	300g Aerosol
CT-R56-400G	400g Aerosol
CT-R56-1L	1L Bottle
CT-R56-5L	5L Bottle
CT-R56-20L	20L Drum

### PRODUCT DESCRIPTION

Chemtools® DEOX R56 Super Lubricant is a silicone-free blend of high quality petroleum distillates, formulated to ensure maximum lubrication, corrosion prevention, and all-weather moisture displacement across a wide and varied array of applications. As a general maintenance penetrant, it arrives unmatched in its versatility and quality, extending the life of parts and machinery, and lubricating moving components.

DEOX R56 can be applied to loosen rusted bolts and stop squeaky hinges, preserve hand tools, ensure the smooth operation of locks and door handles, and protect operating controls, electrical wiring, ignition systems, circuitry, connectors, and much more.

DID YOU KNOW... DEOX R56 performs well as a cutting oil, and is a great environmental barrier to protect and preserve outdoor structures and equipment from harsh winds, weathering, and humidity extremes. It is an ideal lubricant for bicycle and automotive suspension components, and comes equipped with an Accu-Jet valve (400g Aerosol only) with extension tube for hard-to-reach areas.

### DIRECTIONS

Remove all contaminants from the surface before applying.

Spray from a distance of approximately 250mm to 300mm.

Wash contacted areas thoroughly after handling.

Note: Use in a well ventilated area. For best results, use at room temperature (21°C).



# TECHNICAL DATA SHEET

## A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

### TECHNICAL DATA

Temperature Range	-15°C to +188°C
Load Capacity	Low
Appearance	Light translucent yellow
Odour	Sweet
Aerosol Propellant	400g: Hydrocarbon, 150g/300g: Carbon Dioxide
Specific Gravity	0.82
Shelf Life:	3 years from date of manufacture

### SAFETY PRECAUTIONS (REFER TO SAFETY DATA SHEET BEFORE USE)

Use personal protective equipment (PPE) as required. Refer to Safety Data Sheet for full details.

Store below 30°C. Protect from direct sunlight. Do not expose to temperatures exceeding 50°C. Store in a dry place in a closed container.

**FIRST AID:** Call a POISONS CENTER or doctor if you feel unwell, have been affected, or are concerned.

### DISCLAIMER

Chemtools® has made every effort to ensure the information provided in this Technical Data Sheet is accurate at the time of publication. Chemtools® expressly recommends that the user make his/her own assessment to determine the suitability of the product for its intended purpose prior to application. Chemtools shall not be responsible for loss, damage, or injury, resulting from the reliance upon, or failure to adhere to, any recommendations or information contained herein; nor from abnormal use of the material; nor from any hazard inherent in the nature of the material.

### FURTHER INFORMATION

Please visit Chemtools® online at [www.chemtools.com.au](http://www.chemtools.com.au) for product photos, marketing materials, Technical Data Sheets, Safety Data Sheets, contact details, and other company/business related information.