

RENOLIT LEP 2 HD

Heavy duty EP grease for heavily loaded applications.

Description

RENOLIT LEP 2 HD is a heavy duty extreme pressure grease containing a high viscosity mineral oil, lithium thickener, special EP additive, rust and oxidation inhibitors and tackiness agent.

RENOLIT LEP 2 HD provides excellent stay-in-place properties which makes the grease particularly suitable for Mining, Automotive and Industrial equipment applications operating under arduous conditions.

Application

- Mining and quarrying
- Heavy duty transport
- Chassis lubrication
- Construction equipment
- Heavy industrial
- Dredging equipment
- Agricultural and forestry

Advantages/Benefits

- Excellent resistance to water washout ensures lubrication is maintained under extremely wet conditions
- Extended service intervals due to superior retention properties which resists leakage and environmental ingress under high load conditions
- Outstanding film strength and effective EP additives protect against component wear under severe environmental and shock loading conditions
- Protects against corrosion with highly effective inhibitors, even under extreme wet conditions"
- Reduces maintenance costs

Product Information



CHARACTERISTICS

Appearance	Visual	Red	-
NLGI-grade	-	2	-
Thickening agent	-	Lithium soap	-
Worked Penetration x 60 @ 25 °C	ASTM D217	280	mm ² /s
Timken EP Test for Greases, OK Load	ASTM D2509	32	kg
Kinematic Viscosity @ 40 °C	ASTM D445	430 (base oil)	cSt
Dropping Point	ASTM D2265	180	°C

Product Code: 3421
Last Update: 02/06/2016