

## RENOLIT EP 00

**Semi-fluid "self-levelling" industrial grease with extreme pressure additives for severe service and high load applications.**

### Description

RENOLIT EP 00 is a semi-fluid "self-levelling" industrial grease with extreme pressure additives for severe service and high load applications. RENOLIT EP 00 is self-sealing and the non-drip characteristic forms a protective seal preventing ingress of contaminants. RENOLIT EP 00 is compatible with most seal material, having minimal effect on rubber seals

### Application

RENOLIT EP 00 is recommended for lubrication of plain and roller bearings, open and closed gear boxes and in centralized lubrication systems especially where good pumpability is required.

### Advantages/Benefits

### Specifications

### Approvals

- Declaration - Hazardous Substance - Meat

### FUCHS Recommendations

# Product Information



## CHARACTERISTICS

Appearance	Visual	brown	-
NLGI grade	-	00	-
Thickener	-	Lithium Soap	-
Worked Penetration x 60 @ 25 °C	ASTM D217	400-430	0.1 mm-
Dropping Point	ASTM D2265	152	°C
Four Ball EP Test - Weld Load	ASTM D2596	315	kgf
Base Oil Viscosity @ 40 °C	ASTM D445	220	cSt
Base oil Viscosity @ 100°C	ASTM D445	15	cSt
Working Range	-	100 Max.	°C

Product Code: 1955  
Last Update: 26/08/2020