

## RENOLIT GT-PLEX 2

**Tacky high performance lithium complex grease**

### Description

RENOLIT GT-PLEX 2 is a high performance multi-purpose grease. It has been designed for high temperature applications and to stay in place and resist water wash out. RENOLIT GT-PLEX is orange in color for easy identification and will resist squeeze-out whilst also preventing wear and corrosion. Due to the design of this product, it provides an effective seal against contamination ingress such as dust, dirt and water which also assists in reducing grease consumption and prolonging the life of the components which are lubricated using this state of the art orange grease.

### Application

Plain and roller bearings which are subject to a wide range of conditions such as high and low operating temperatures, water, dirt and humidity. An excellent choice as a multi-purpose grease for industries such as mining, agriculture, construction, earthmoving, passenger cars and commercial vehicles.

### Advantages/Benefits

- Multi-purpose
- Shear stable
- Extreme Pressure / Anti-Wear / Corrosion Protection
- Orange in color for easy identification
- Tacky
- Excellent corrosion protection
- Prevents wear in harsh conditions
- Resists squeeze out

### Specifications

- NLGI 2

### Approvals

### FUCHS Recommendations

# Product Information



## CHARACTERISTICS

NLGI-grade	-	2	-
Thickener	-	Lithium Complex	-
Texture	-	Tacky	-
Colour	-	Orange	-
Worked penetration (Pw 60)	ASTM D217	265-295	1/10mm
Dropping Point	IP296	>260	°C
Weld Load	ASTM D2596	>315	kgf
Base Oil Viscosity @ 40 °C	ASTM D2266	220	cSt

Product Code: M5073888  
Last Update: 28/03/2022