

## drum based oil dispensing systems

Designed for simple, single point oil dispensing, the drum based oil dispensing systems provide performance and convenience.



All systems are available without a gun. Please refer to price list.



	R100THG-01	R100THGE-01	R300THG-01	R300THGE-01
Pump ratio	1:1	1:1	3:1	3:1
Pump	R100T-01	R100T-01	R300T-01	R300T-01
Outlet hose length	3m x 3/4"	3m x 3/4"	3m x 1/2"	3m x 1/2"
Oil control gun	HG20R-01	HG20R-012E-01	HG20R-01	HG20R-012E-01
Output SAE10*	12 L/min	12 L/min	12 L/min	12 L/min
Output 15W-40*	9 L/min	9 L/min	9 L/min	9 L/min
Output SAE140*	8 L/min	8 L/min	8 L/min	8 L/min
Container	205L drum	205L drum	205L drum	205L drum
Airline lubricator	■	■	■	■
Pressure relief valve	-	-	-	-
2" bung adapter	■	■	■	■
Fully serviceable	■	■	■	■
Warranty <sup>1</sup>	10 years	10 years	10 years	10 years
Parts guarantee <sup>2</sup>	10 years	10 years	10 years	10 years
Compatible fluids	oils up to SAE140, automatic trans fluid, engine oil, gear oil, hydraulic oil, diesel, kerosene, anti-freeze/anti-boil			
Wetted components	aluminium, Nitrile rubber, carbon PFTE, zinc plated carbon steel and brass			
Max air pressure	1030kPa (150psi)	1030kPa (150psi)	1030kPa (150psi)	1030kPa (150psi)
Min air pressure	400kPa (60psi)	400kPa (60psi)	400kPa (60psi)	400kPa (60psi)
Min air compressor	0.22m³/min (8cfm)	0.22m³/min (8cfm)	0.16m³/min (6cfm)	0.16m³/min (6cfm)
Air inlet	1/4" NPT (F)	1/4" NPT (F)	1/4" NPT(F)	1/4" NPT(F)

Note\* Pump tested at 100psi c/w HG55 oil control gun.

Note<sup>1</sup> Subject to Macnaught warranty terms and conditions, see inside back cover.

Note<sup>2</sup> Parts available for 10 years from deletion or upgrade of model.