

## REFILLABLE SINGLE POINT GREASE LUBRICATOR - 220ML

**12**  
MONTHS  
MACNAUGHT  
WARRANTY

Designed to provide consistent lubrication in hard to reach, hidden, or easy to forget greasing points on fixed plant machinery, conveyor systems, process machinery, block bearings, bushings and joints.

The lubricators are supplied with a timing dial adjustable between 1, 3, 6 or 12 months to set dispense rate as well as two silver pressure springs to accurately adjust for grease viscosity and temperature. The lubricators can be easily filled through the grease nipple located on the side of the lubricators.

Made from UV stable, impact resistant Lexen® these continuous bearing lubricators can be mounted in any orientation and provide refillable longevity in temperatures from -23°C to 132°C.

### Strong Transparent Lexen®

Easy to see grease level

### Grease Nipple (Filling Point)

Easy filling using standard grease gun

### Flow Adjustment Screw



### Supplied with 2 Springs

Heavy gauge spring - Strong tension  
Lighter gauge spring - Medium tension

### 220ml Capacity

For greases up to NLGI No.2

### 1/8" BSP Adaptor

Fitted at the bottom of the M10X1 thread

MCGL220-01

### TECHNICAL SPECIFICATIONS

- 220ml capacity
- Compatible with grease viscosities up to NLGI 2
- Temperature range: -23°C to 132°C
- Outlet thread: 1/8" BSP with an adaptor to M10x1

### PACKAGE INCLUDES

- Automatic lubricator
- Additional pressure spring

### APPLICATIONS

- Hidden or hard to access greasing points, fixed plant machinery, conveyor systems, process machinery, block bearings, bushings and joints.