

RENOLIT RED RUBBER GREASE

Speciality "Rubber Grease" and "Petrol Resistant Grease"

Description

RENOLIT RED RUBBER GREASE is a specialty lubricant manufactured from prime vegetable oils thickened with a non-soap thickener. A red dye has been added for identification purposes.

RENOLIT RED RUBBER GREASE retains its consistency even at high temperatures and has no drop point in the normal sense of the test. It does not change materially under working conditions or temperature fluctuations and as such resists leakage and dripping.

This grease conforms to major international component manufacturers' specifications for "Rubber Grease" and "Petrol Resistant Grease".

RENOLIT RED RUBBER GREASE is designed to be resistant to most seals used in automotive break assemblies

Application

Automotive brake assemblies
Hydraulic components
Rubber components
Petrol resistant application
Dry cleaning plants
Lubricating oil resistant e.g. gland packing seals

Advantages/Benefits

- Compatibility with natural rubbers
- Compatibility with synthetic rubbers
- Good mechanical stability
- High chemical resistance
- Resistance to hydrocarbons
- Resistance to rubber swell

Product Information



CHARACTERISTICS

| | | | |
|---------------------------------|------------|-----------------------|------------------|
| Appearance | Visual | Red grease | - |
| Texture | - | Medium fibrous grease | - |
| Dropping Point | ASTM D2265 | Infusible | °C |
| Worked Penetration x 60 @ 25 °C | ASTM D217 | 250-290 | mm ⁻¹ |
| NLGI-grade | - | 2/3 | - |
| High temperature stability | - | No gumming | - |
| Cast iron corrosion | - | Nil | - |
| Working Range | - | -10 to 100°C | °C |

Product Code: 2883
Last Update: 25/05/2016