

Retracta R3 Series

WELDING GAS - OXY/ACET

10
YEARS
MACNAUGHT
WARRANTY*

The Retracta R3 Oxy/Acetylene reel is supplied with twin gas hose, made from reinforced rubber compliant to AS 1335 to ensure outstanding support in the welding environment. RACR version also available.

Unique patented RACR
(on selected models)

Working pressure
175psi

UNF Gas Thread



Twin 5mm (3/16") ID hose

Reinforced Rubber
(AS1335) Hose

Why choose this product?

Built for peace of mind reliability, performance and safety

Standard	OA215B-04
RACR® 	OAC215B-04
Case Colour	Blue
Hose Size (ID)	Twin 5mm (3/16")
Hose Length	15m
Hose Material	Reinforced Rubber (AS1335)
Working Pressure	175 psi
Max Temperature	80°C (176°F)
Reel Inlet	Gas Thread UNF (M)
Hose Outlet	Gas Thread UNF (F)

Features & Benefits

- Highly durable Double Reinforced Rubber
- Upgraded main spring made with TRC – Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully serviceable
- RACR® – on selected models

Applications:

Suitable for use in all industries where Oxy /Acetylene is required

Service Parts:

- See Page 252 for service kits and parts

Recommended to
be used with:



BB200 R3 Bench
Mount Bracket