

SILKOLENE PRO KR2

Castor and ester synthetic 2-Stroke engine oil for kart racing

Description

SILKOLENE PRO KR2 combines the outstanding wear and load carrying properties of castor oil with clean burning modern synthetics technology, to give exceptional engine performance, sustained power output and reliability.

Advantages / Benefits

- CIK-FIA Homologated
- Excellent anti-wear protection to engines
- Synthetic fortified castor blend

Application

SILKOLENE PRO KR2 is the ideal lubricant for all high output liquid and air-cooled kart engines. It is suitable for use with all gasoline and alcohol fuels.

Do **not** mix SILKOLENE PRO KR2 with other lubricants.

For dilution ratios, consult manufacturers recommendations.

Specifications/Approvals

- SILKOLENE PRO KR2 meets the stringent test requirements of the CIK-FIA (COMMISSION INTERNATIONALE DE KARTING - FEDERATION INTERNATIONALE DE L'AUTOMOBILE) and is a CIK-FIA approved (homologated) lubricant.

FUCHS LUBRICANTS (UK) PLC

New Century Street, Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU
Tel: +44 (0)1782 203 700
Email: contact-uk@fuchs-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Health, Safety and Environmental information is provided for this product in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

Typical Data: SILKOLENE PRO KR2

Characteristics	Test Method	Unit	
Colour	Visual		Dark orange / Red
SAE Grade			30
Specific Gravity at 15°C	IP160		0.944
Kinematic Viscosity at 40°C	IP71	mm ² /s	95.9
Kinematic Viscosity at 100°C	IP71	mm ² /s	11.1
Viscosity Index (VI)	IP226		101
Pour point	IP15	°C	-35
Flash Point (Closed Cup)	IP34	°C	200