

THE STANDOUT IN THE FIELD

ROTARY LASER

GREEN BEAM

RED BEAM

i88G

i88R

The i88 series is the most versatile and feature-packed rotary laser in the iMEX range. With manual dual slope and available in red or green beam to suit both indoor and outdoor use.



Features

- Self-levelling
- 600m diameter range
- 1.5mm accuracy @ 30m
- Manual dual slope model
- 4 rotation speeds
- Horizontal/ vertical operation
- Scan mode for site shielding and concentrated levelling
- 9Ah lithium-ion battery

- LRX10 German made mm reading detector with 90mm pick-up
- Detector measures in 0.5mm,1mm,2mm, 5mm, 10mm increments
- High wind sensitivity override- resets to compensate high wind
- IP66 water resistant and shockproof

Best for



5 YEARS

WARRANTY



CALIBRATION VERIFIED




LITHIUM BATTERY



DIGITAL DETECTOR



QUICK CHARGE



LRX10 Detector

SPECIFICATIONS

i88G 012-i88G, i88R 012-i88R

Self Levelling Range	+/- 5°	USB Charging	Yes; including 12v car charger
Accuracy	+/- 1.5mm @ 30m	High Wind Sensitivity Re-set	Yes
Working Distance	600m diameter	Remote Control	Yes, iCR8
Function	Horizontal/Vertical	Weight-Unit Only	2.48Kg
Scan Mode	Yes, 0°, 10°, 45°, 90°, 180°	Detector - German Made	LRX10 Double sided
Slope Mode	Yes - Dual manual grade to 5° 9%	Detector Pick-Up	90mm -30mm to +60mm
Rotation Speeds	0, 60, 120, 300, 600 rpm	Detector Reading	Ultra fine - 0.5mm; Fine - 1.0mm; Medium - 2.0mm; Course - 5.0mm; Ultra Course - 10.0mm
Light Source	Green 535nm/Red 635nm Class II	Detector Power	1-AA > 50 hrs run
Water Resistant, Shockproof	IP66	Inclusions	Unit, LRX10 Detector, Remote control unit, USB cable, 9.0 Ah Lithium battery, Spare charger, Car charger, target plate, hard carry case
Power Source	9 Ah 3.7v lithium-ion		
Working Time Continuous Use	24hrs approx Green, 40hrs approx Red		
Charging Time	4 hrs		