

TITAN ATF 4400

Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles. The high torque capacity exceeds the performance of many original fluids. Product dyeing: Red.

Description

TITAN ATF 4400 has been developed especially to suit the special demands of modern Japanese steptype automatic transmissions with hydraulic converters used in many passenger cars and light duty vehicles.

TITAN ATF 4400 combines excellent anti-shudder-properties with a high friction-level constant over lifetime. For this profile selected high quality base-stocks have been combined with a specially developed additive technology.

Application

TITAN ATF 4400 is mainly designated for use in the latest generation of AISIN-WARNER-automatic transmissions. These transmissions are being used in a large number of passenger cars and light duty vehicles of Japanese make, but also being used in a significant number of US-American and European models.

Due to its outstanding properties TITAN ATF 4400 can also be used in many aggregates of Asian origin or where DEXRON III-type fluids are demanded. TITAN ATF 4400 is miscible and compatible with conventional branded ATFs. However, mixing with other transmission oils should be avoided because this can eliminate the benefits offered. We recommend that manufacturer's oil change intervals should be observed to generate the best possible economy and service life.

Advantages/Benefits

- Best anti-wear-properties for reliable operation and maximum lifetime
- High friction level constant over lifetime
- Outstanding ageing and oxidation stability
- Selected base oils offer excellent cold-temperature properties

Product Information



Specifications

- JASO M315 TYPE 1A

Approvals

- -

FUCHS Recommendations

- AISIN WARNER / AW-1
- BMW MINI 83 22 0 402 413 / 83 22 7 542 290
- CHRYSLER MS7176E/9602 (ATF +3 / +4)
- DAEWOO
- DAIHATSU ALUMIX ATF MULTI
- dexron® III
- FIAT 9.55550-AV1/AV2/AV4
- FORD MERCON / M2C924-A / M2C922-A1
- GM 9986195
- HONDA ATF Z-I
- HYUNDAI SP-III/IV
- ISUZU BESCO ATF-II/ATF-III
- JATCO 3100 PL085/ FWD (N402) / JF506E (K17)
- JWS 3309/TYP T-IV
- KIA SP-IV
- MAZDA ATF D-III/ATF M-3
- MITSUBISHI SP-II-/III
- NISSAN C/D/J/S
- SAAB 3309
- SUBARU ATF OIL/ATF OIL SPECIAL/ ATF HP
- SUZUKI ATF 3309/3317
- TOYOTA TYPE D-2/WS
- TOYOTA TYPE T/T-II/T-III/T-IV
- VW G 052 990/055 025

CHARACTERISTICS

Appearance	Visual	Clear Red Liquid	-
Density @ 15 °C	DIN 51757	0.849	Kg/L
Kinematic Viscosity @ 40 °C	ASTM D445	40	cSt
Kinematic Viscosity @ 100 °C	ASTM D445	7.2	cSt
Viscosity Index	ASTM D2270	150	-
Pour Point	FLTP* 124	< -45	°C
Flash Point, COC	ASTM D92	195	°C

Product Code: 3970
Last Update: 13/06/2017