

TITAN ATF 5500

Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent shift performance.

Description

TITAN ATF 5500 has been designed based on selected high-quality base oils and a specially developed additive technology. It is highly thermally durable, offers extreme oxidation stability and offers also a reliable performance at very low temperatures. TITAN ATF 5500 is applicable in many applications in passenger cars as well as light and heavy duty vehicles.

Application

TITAN ATF 5500 is recommended for use in automatic transmissions, hydraulic converters, Retarders, turbo-couplings, powershift-transmissions, hydraulic and power steering systems as well as many other applications demanding the specifications listed in this document. TITAN ATF 5500 is miscible and compatible with conventional branded gear oils. However, mixing with other gear oils should be avoided in order to fully utilise the product's benefits. A complete oil change is recommended when converting to TITAN ATF 5500. For information on product safety and proper disposal please refer to the latest Safety Data Sheet.

Advantages/Benefits

- Excellent performance in cold- and very high temperature operation

- High friction level constant over lifetime for out-standing shift-performance
- Outstanding ageing-protection and oxidation stability prevents from oil thickening, deposits and achieves maximum drain intervals
- Best anti-wear-properties for reliable operation also in continuous operation
- Wide operational spectrum covering passenger as well as heavy-duty vehicles

Specifications

- -

Approvals

- EvoBus 27.000-017
- MAN 339 TYPE V1/V2/Z3/Z12
- MB-APPROVAL 236.9
- VOITH 150.014524.xx
- VOLVO 97341
- ZF TE-ML 04D, 14C, 16M, 16S, 20C, 25C (ZF001797)

FUCHS Recommendations

- ALLISON TES 295, 389
- DEXRON III (H)
- IVECO 18-1807 CLASSE AG3/I
- MAN 339 TYPE Z4

Product Information



CHARACTERISTICS

Density @ 15°C	DIN 51 757	0.842	g/ml
Flashpoint CoC	DIN ISO 2592	238	°C
Pour Point	DIN ISO 3016	-48	°C
Kinematic Viscosity @ 40°C	DIN 51 562-1	39.0	mm²/s
Kinematic Viscosity @ 100°C	DIN 51 562-1	7.28	mm²/s
Viscosity Index	DIN ISO 2909	153	-

Product Code: 4845
Last Update: 03/11/2021