

TITAN FORMULA SP 20W-50

All season, high performance SAE 20W-50 engine oil.

Description

All season high performance SAE 20W-50 engine oil. For normally aspirated and turbo-charged petrol engines and light commercial diesel engines.

Application

Miscible with all mineral oil and synthetic oil, therefore no flushing required. Provides excellent viscometrics and maintains engine cleanliness. Suitable for vehicles using LPG fuel, leaded and unleaded fuel. Also compatible with catalytic converters.

Advantages/Benefits

- Compatible with all gaskets and seals
- Compatible with catalytic converters
- Excellent protection against wear and maintains engine cleanliness
- Optimum operation of tappets due to the absence of foam

- Protects against sludging
- Provides excellent viscometrics: stays in grade and maintains its characteristics even in very severe operations
- Suitable for vehicles operating in dusty or sandy conditions, stop-start driving
- Suitable for vehicles using LPG, diesel, leaded and unleaded fuel

Specifications

- API SP / CF

Approvals

FUCHS Recommendations

Product Information



CHARACTERISTICS

Density @ 15 Deg C	DIN 51757	0.88	Kg/L
High Temperature High Shear (HTHS)	ASTM D4683	> 3.7	N/A
Viscosity Index	ASTM D2270	> 115	N/A
Kinematic Viscosity @ 100 Deg C	ASTM D445	18.0 typ.	cSt

Product Code: M5088000
Last Update: 27/05/2022