

Product Information

MOVING YOUR WORLD



FRICOFIN MP

High Performance, long-life anti-freeze, anti-boil engine multi-purpose coolant concentrate, free of nitrites, borates and silicates with 2-EHA free, x-OAT-technology.

Description

As a x-OAT coolant concentrate it provides a stable inhibitor system based on organic acids (OAT) for maximum drain intervals and a small concentration of inorganic inhibitors (X) to accelerate the performance.

Application

FRICOFIN MP is recommended for use in light and heavy-duty automotive applications as well as many off-highway constructions and agricultural applications. FRICOFIN MP is excellent for use where a coolant with OAT technology is required.

FRICOFIN MP is recommended for use between 33% and 50% concentration in good quality water.

For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages

- Free of 2-EHA, nitrites, borates and silicates
- High protection against freezing and overheating.
- Suitable for mixed fleets
- Compatible with seals, plastics and non-ferrous metals.
- Long-lasting protection against deposits, cavitation and corrosion in engines and coolers.
- Contains bittering agent to prevent swallowing.

Specifications

- ASTM D3306-20 Type I
- ASTM D 4985
- AS/NZS 2108:2004 TYPE A
- BS 6580:2010
- SAE J1034

Approvals

▪ -

Product Information

MOVING YOUR WORLD



FUCHS Recommendations

- CASE MS 1710
- DETROIT DIESEL 7SE298
- FORD ESE-M97B44-A
- FORD ESE-M97B18-C
- FORD WSS M97B51-A1
- GM 1825M/GM 1899M
- GM HN 2217
- JASO M325
- JIS K 2234
- MAN 324 TYPE SNF
- MAZDA MEZ MN 121 D
- MB 325.3 / DTFR 29C120
- NEW HOLLAND WSN-M97B18-D
- SAAB 690 1599
- TMC RP 329

Product Information

MOVING YOUR WORLD



TYPICAL CHARACTERISTICS

Density at 20°C	ASTM D 5931	1.07 g/ml
pH-value	ASTM D1287	8.6
Colour	Visual	Green

Product Information

MOVING YOUR WORLD



The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (AUSTRALASIA) in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircrafts/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (AUSTRALASIA) application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (AUSTRALASIA).