

Product Information

MOVING YOUR WORLD



TITAN FORMULA SQ SEM 10W-30

Ultra High Performance fuel-economy engine oil for a variety of petrol engines in passenger cars.

Description

TITAN FORMULA SQ SEM 10W-30 is a high performance, all season, fuel economy engine oil designed for normally aspirated and turbocharged cars and vans with petrol engines. Meets the following performance requirements: API SQ and ILSAC GF-7.

Application

TITAN FORMULA SQ SEM 10W-30 is miscible and compatible with conventional, branded engine oils. However, mixing with other engine oils should be avoided in order to fully exhaust this product's benefits. A complete oil drain is recommended when converting to TITAN FORMULA SQ SEM 10W-30.

Advantages

- Superior oil circulation after start-up improves cold-start properties and reduces warm-up wear.
- Improved protection against sludge formation.
- Excellent anti-wear protection.
- Improved fuel economy because of its low viscosity and cold-temperature properties.

Specifications

- API SQ
- ILSAC GF-7

Approvals

- -

FUCHS Recommendations

- API SP / CF

Product Information

MOVING YOUR WORLD



TYPICAL CHARACTERISTICS

Density at 15°C	DIN 51757	0.859 Kg/L
KV100	ASTM D445	10.9 cSt
Viscosity index	ASTM D 2270	>140
HTHS	ASTM D4683	>2.9

Product Information

MOVING YOUR WORLD



The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (AUSTRALASIA) in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircrafts/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (AUSTRALASIA) application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (AUSTRALASIA).